

iSeries IS2300 to IS2611 USB 3.2 Cables

Yesterday a data cable, today a video cable, tomorrow... - Who knows?!

USB-C has the potential to replace every popular connector you know. Using the DisplayPort Alt-mode, the functions of all interfaces can automatically adapt to USB-C, enabling data, AV and power transmission over one single standard. The iSeries USB 3.2 connection cables were designed to take full advantage of this flexibility to meet any modern connectivity challenge. The cables allow you to power devices with up

to 100W and a variable voltage, using the USB Power Delivery standard. They also provide a data transfer rate up to 10Gbps, making them suitable for a direct AV connection to digital displays with a variety of video formats. We promise nothing less than the best possible product quality, verified by the strictest PureLink testing standards.



USB 3.2 Cable Range

With the iSeries, PureLink offers a comprehensive range of USB 3.2 connection cables with USB-C, USB-A or USB-B connectors - available in black or white.

Large Selection

Colour selection white / black in lengths between 0.50 and 2.00 meters. All versions are available as 5Gbps version according to USB 3.2 Gen1 or as 10Gbps version according to USB 3.2 Gen2 standard.

One Single Standard

Enable your devices to transfer AV streams, power incl. USB Power Delivery, control signals as well as general data signals via the USB-C Alt-mode.

High Quality Finish

Precisely fitting, high-quality connectors with gold-plated contacts round off the state-of-the-art electronics, thus enabling the multifunctional signal transmission.

Future-Proof Cable Technology

With high-purity inner copper conductors and a triple shielding structure, the transmission quality is permanently verified. Connect and forget.

Retail Optimised Packaging

The high-quality, multilingual packaging stands out at every point of sale due to its attractive design, while being optimised for warehousing and perfect product protection.



Product Overview

IS2300 to IS2611 USB 3.2 Cables

	Parent	Art. No.	Length	Connector	Description
	IS2300	IS2300-005	0.50m	USB-A ↔ USB-B	USB 3.2 (Gen2) cable with 10Gbps, USB-A male to USB-B male, 3A/5V/15W max. power output white
		IS2300-010	1.00m		
		IS2300-015	1.50m		
		IS2300-020	2.00m		
		IS2300-030	3.00m		
	IS2301	IS2301-005	0.50m	USB-A ↔ USB-B	USB 3.2 (Gen2) cable with 10Gbps, USB-A male to USB-B male, 3A/5V/15W max. power output black
		IS2301-010	1.00m		
		IS2301-015	1.50m		
		IS2301-020	2.00m		
		IS2301-030	3.00m		
	IS2310	IS2310-005	0.50m	USB-C ↔ USB-B	USB 3.2 (Gen2) cable with 10Gbps, USB-C male to USB-B male, 3A/5V/15W max. power output white
		IS2310-010	1.00m		
		IS2310-015	1.50m		
		IS2310-020	2.00m		
	IS2311	IS2311-005	0.50m	USB-C ↔ USB-B	USB 3.2 (Gen2) cable with 10Gbps, USB-C male to USB-B male, 3A/5V/15W max. power output black
		IS2311-010	1.00m		
		IS2311-015	1.50m		
		IS2311-020	2.00m		
	IS2400	IS2400-005	0.50m	USB-A ↔ USB-A	USB 3.2 (Gen1) cable with 5Gbps, both sides with USB-A male connectors, 3A/5V/15W max. power output white
		IS2400-010	1.00m		
		IS2400-015	1.50m		
		IS2400-020	2.00m		
	IS2401	IS2401-005	0.50m	USB-A ↔ USB-A	USB 3.2 (Gen1) cable with 5Gbps, both sides with USB-A male connectors, 3A/5V/15W max. power output black
		IS2401-010	1.00m		
		IS2401-015	1.50m		
		IS2401-020	2.00m		
	IS2410	IS2410-005	0.50m	USB-A ↔ USB-A	USB 3.2 (Gen2) cable with 10Gbps, both sides with USB-A male connectors, 3A/5V/15W max. power output white
		IS2410-010	1.00m		
	IS2411	IS2411-005	0.50m	USB-A ↔ USB-A	USB 3.2 (Gen2) cable with 10Gbps, both sides with USB-A male connectors, 3A/5V/15W max. power output black
		IS2411-010	1.00m		

Product Overview

IS2300 to IS2611 USB 3.2 Cables

	Parent	Art. No.	Length	Connector	Description
	IS2500	IS2500-005	0.50m	USB-C ↔ USB-C	USB 3.2 (Gen1) cable with 5Gbps, both sides with USB-C male connectors, E-Marker, USB PD with 3A/20V/60W, DP Alt-Mode white
		IS2500-010	1.00m		
		IS2500-015	1.50m		
		IS2500-020	2.00m		
	IS2501	IS2501-005	0.50m	USB-C ↔ USB-C	USB 3.2 (Gen1) cable with 5Gbps, both sides with USB-C male connectors, E-Marker, USB PD with 3A/20V/60W, DP Alt-Mode black
		IS2501-010	1.00m		
		IS2501-015	1.50m		
		IS2501-020	2.00m		
	IS2510	IS2510-005	0.50m	USB-C ↔ USB-C	USB 3.2 (Gen2) cable with 10Gbps, both sides with USB-C male connectors, E-Marker, USB PD with 5A/20V/100W, DP Alt-Mode white
		IS2510-010	1.00m		
		IS2510-015	1.50m		
	IS2511	IS2511-005	0,50m	USB-C ↔ USB-C	USB 3.2 (Gen2) cable with 10Gbps, both sides with USB-C male connectors, E-Marker, USB PD with 5A/20V/100W, DP Alt-Mode black
		IS2511-010	1,00m		
		IS2511-015	1,50m		
	IS2512	IS2512-005	0,50m	USB-C ↔ USB-C	USB 3.2 (Gen2) cable with 10Gbps, both sides with USB-C male connectors, with USB-A attachment (to be attached to the USB-C plug), E-Marker, USB PD with 5A/20V/100W, DP Alt-Mode white
		IS2512-010	1,00m		
	IS2513	IS2513-005	0,50m	USB-C ↔ USB-C	USB 3.2 (Gen2) cable with 10Gbps, both sides with USB-C male connectors, with USB-A attachment (to be attached to the USB-C plug), E-Marker, USB PD with 5A/20V/100W, DP Alt-Mode black
		IS2513-010	1,00m		

Product Overview

IS2300 to IS2611 USB 3.2 Cables

	Parent	Art. No.	Length	Connector	Description
	IS2600	IS2600-005	0.50m	USB-C ↔ USB-A	USB 3.2 (Gen1) cable with 5Gbps, USB-C male to USB-A male, 3A/5V/15W max. power output white
		IS2600-010	1.00m		
		IS2600-015	1.50m		
		IS2600-020	2.00m		
	IS2601	IS2601-005	0.50m	USB-C ↔ USB-A	USB 3.2 (Gen1) cable with 5Gbps, USB-C male to USB-A male, 3A/5V/15W max. power output black
		IS2601-010	1.00m		
		IS2601-015	1.50m		
		IS2601-020	2.00m		
	IS2610	IS2610-005	0.50m	USB-C ↔ USB-A	USB 3.2 (Gen2) cable with 10Gbps, USB-C male to USB-A male, 3A/5V/15W max. power output white
		IS2610-010	1.00m		
	IS2611	IS2611-005	0.50m	USB-C ↔ USB-A	USB 3.2 (Gen2) cable with 10Gbps, USB-C male to USB-A male, 3A/5V/15W max. power output black
		IS2611-010	1.00m		

Kontakt

PureLink GmbH
Von-Liebig-Str. 10
48432 Rheine | Germany

☎ +49 5971 800 299-0
📠 +49 5971 800 299-99
✉ info@purelink.de



All information is subject to confirmation and non-binding.
Technical changes, printing errors and mistakes excepted.
All data as of Februar 2025