

RMS 0550



Key Features

- 5.5" LCD screen, resolution up to 1920×1080
- 4K HDMI input&loop output
- Embedded audio
- Pixel-to-pixel
- Image flip, freeze and other adjustment
- Flexible built-in dual-purpose battery plate

Specification

Connectors	Input	1×HDMI-A
	Output	1×HDMI-A
	Audio	1×Stereo
	Power	2×DC Jack (1 In 1 Out)
Performance	Supported Resolutions	480i/576i/480p/576p
		1080i (60/59.94/50)
		720p (60/59.94/50/30/29/25/24/23.98)
		1080p(60/59.94/50/30/29.97/25/24/24sF/23.98/23.98sF)
		4K UHD 3840×2160p (30/29.97/25/24/23.98Hz), 4096×2160p (24Hz)
Screen	Screen Size	5.5"
	Display Color	16.7M (8 bit)
	Resolution	1920×1080 pixels
	Dot Pitch	0.0639 (H)×0.0213 (W) mm
	Aspect Ratio	16:9
	Brightness	500cd/m ²
	Contract	1000:1
	View Angle	80°/80°(L/R) 80°/80°(U/D)
Functions	Color Adjustment	Histogram
		Peaking Filter
		False Color
		Exposure
	Image Adjustment	Nide Grid
		Image Flip
		Image Freeze
Anamorphic Mode		
Zoom-in		
Power	Consumed Power	≤9W
	Input Power	DC 6~24V
	Battery Gusset Plate	F970/ LP-E6 Dual-purpose Battery Plate
Environment	Working Temperature	-20°C ~ 55°C
	Store Temperature	-30°C ~ 65°C
Physical	Weight	175g
	Dimension	142L×87.2H×27.5D (mm)

Order Code

Product Code	Item
400-0550-01-0	RMS 0550

